SWEET-SPOT ADVENTURER

Elevate your next expedition with the all-new TRK 702 touring model

Benelli





TRK 702

SPECIFICATIONS

ENGINE

Type
2-cylinder/4-stroke/4-valve
Valve Train
DOHC
Bore & Stroke
83 x 64,5 mm.
Displacement
698 c.c.
Rated Output
51,5kW/8000rpm
Compression Ratio
11.6:1
Gearbox
6-speed
Lubrication
Pressure splash lubrication
Clutch
Wet multi-plate
Fuel System
EFI
Exhaust System
Long-acting Catalyst and Oxygen Sensor
Starting
Electric
Cooling System
Liquid-cooled
Ignition
Delphi MT 05 TLI
Fuel Capacity
20lt

CHASSIS

Frame
Steel-tube trellis chassis
Front Suspension
50 mm upside-down forks, 140 mm stroke
Rear Suspension
45 mm Rear wheel travel 154mm
Front Brake
320mm disc with four-piston caliper, ABS
Rear Brake
260mm disc with single-piston caliper, ABS
Front Wheel
17 × 3.5 inch
Rear Wheel
17 × 4.5 inch
Front Tyre
120/70R17
Rear Tyre
160/60R17
Wheelbase
1505 mm.
Ground Clearance
175mm
Seat Height
790mm
Weight
215kg



WHITE



GREY



GREEN

@BenelliAustralia
@Benelli_Aus_NZ
www.benelli.com.au
www.benellimotorcycles.co.nz

PURE PASSION SINCE 1911

*Motorcycle pictured in lifestyle images is fitted with optional Genuine Benelli Accessories. Benelli Motorcycles Australia reserves the right to vary colours, specifications and pricing at any time. Benelli Australia offers 2 Years Roadside Assistance on all New Benelli motorcycles sold in Australia excluding TNT125 & Benelli E-bikes. Please confirm with your local Benelli dealer for final specifications and pricing at time of purchase.